



# PU Coated 21 ga. HPPE (Cut/Touch Screen)

# PRODUCT DETAILS

- + 21 ga. HPPE/polyester/steel shell
- + Polyurethane palm coating
- + Elastic knit wrist w/hemmed cuff
- + Reinforced thumb saddle



## HAZARD SOLUTIONS

Abrasion Resistant



**Cut Resistant** 



**Puncture Resistant** 

#### **FEATURES**



360 Degree Coverage



Breathable



Dexterity



**Food Contact** 



Solid Grip



Touch Screen

## RATINGS

Cut Level A7 (ANSI/ISEA 105-2024)



Abrasion Level 3 (ANSI/ISEA 105-2024)

Puncture Level 3 (ANSI/ISEA 105-2024)



FDA 21 CFR 175.300

## SIZES

ITEM #	SIZE	UPC
99-1-9571-6	XS (6)	063344446835
99-1-9571-7	S (7)	063344444985
99-1-9571-8	M (8)	063344444992
99-1-9571-9	L (9)	063344445005
99-1-9571-10	XL (10)	063344445012
99-1-9571-11	X2L (11)	063344445029
99-1-9571-12	X3L (12)	063344446842

<sup>\*</sup>Not all styles/sizes available in all regions.

# PACKAGING

- + 12 PR per Polybag 120 PR per Carton
- + Vend Pack Option Available: Yes

\*Bob Dale Gloves products are tested for cut and puncture resistance. These products ARE NOT CUT AND PUNCTURE PROOF. Do not use with moving blades, tools or serrated blades.



BDG® CANADA CORPORATE OFFICE

4504 - 82 Avenue, Edmonton, AB T6B 2S4

PHONE

TOLL-FREE 1 (800) 661-7303 (780) 469-2100 BDG® USA OFFICE

2135 W. Obispo Avenue, Gilbert, AZ, 85233

TOLL-FREE 1-800-661-7303 PHONE (480) 397-0270

12.04.2025 20:32 (UTC-7)

warranties are given other than those implied mandatory by law.

Information contained in this document is subject to change without notice. As Bob Dale Gloves and Imports Ltd. cannot control or anticipate the conditions under which this product may be used, each user should review the information in specific context of the planned use. To the maximum extent permitted by law, Bob Dale Gloves and Imports Ltd., and/or its affiliates, employees or representatives will not be responsible for damages of any nature resulting from the use or reliance upon the information contained in this data sheet. No express or implied

<sup>\*</sup>Not Proposition 65 compliant.