



Nitrile Coated 13 ga. HPPE (Cut)

PRODUCT DETAILS

- + 13 ga. HPPE shell
- + Nitrile palm coating w/textured finish
- + Elastic knit wrist w/hemmed cuff



HAZARD SOLUTIONS



Abrasion Resistant



Cut Resistant



Heat Resistant



Puncture Resistant

FEATURES



360 Degree Coverage



Breathable



Dexterity



Solid Grip

RATINGS



Cut Level A6 (ANSI/ISEA 105-2016)



Abrasion Level 3 (ANSI/ISEA 105-2016)



Puncture Level 4 (ANSI/ISEA 105-2016)



Conductive Heat Level 2, Up to 284° F/140° C (ANSI/ISEA 105-2016)

SIZES

ITEM #	SIZE	UPC
99-1-9626-5	X2S (5)	063344441601
99-1-9626-6	XS (6)	063344394396
99-1-9626-7	S (7)	063344394402
99-1-9626-8	M (8)	063344394419
99-1-9626-9	L (9)	063344394426
99-1-9626-10	XL (10)	063344394433
99-1-9626-11	X2L (11)	063344394440
99-1-9626-12	X3L (12)	063344441052
99-1-9626-13	X4L (13)	063344441076

^{*}Not all styles/sizes available in all regions.

PACKAGING

- + 12 PR per Polybag 120 PR per
- + Vend Pack Option Available: Yes

*Bob Dale Gloves products are tested for cut and puncture resistance. These products ARE NOT CUT AND PUNCTURE PROOF. Do not use with moving blades, tools or serrated blades.



BDG® CANADA CORPORATE OFFICE

4504 - 82 Avenue, Edmonton, AB T6B 2S4

TOLL-FREE 1 (800) 661-7303 (780) 469-2100

BDG® USA OFFICE

2135 W. Obispo Avenue, Gilbert, AZ, 85233

TOLL-FREE PHONE

1 (855) 215-7113

04.23.2024 14:19 (UTC-7)

PHONE

(480) 397-0270

Information contained in this document is subject to change without notice. As Bob Dale Gloves and Imports Ltd. cannot control or anticipate the conditions under which this product may be used, each user should review the information in specific context of the planned use. To the maximum extent permitted by law, Bob Dale Gloves and Imports Ltd., and/or its affiliates, employees or representatives will not be responsible for damages of any nature resulting from the use or reliance upon the information contained in this data sheet. No express or implied warranties are given other than those implied mandatory by law.

^{*}Not Proposition 65 compliant.