




Nitrile Coated 15 ga. Nylon

PRODUCT DETAILS




- + 15 ga. nylon shell
- + Foam nitrile palm coating w/smooth finish
- + Elastic knit wrist w/hemmed cuff






HAZARD SOLUTIONS

-  Abrasion Resistant
-  Heat Resistant
-  Tear Resistant

FEATURES

-  Breathable
-  Dexterity
-  Solid Grip

RATINGS

	EN 388 - 4131X
	EN 407 - X1XXXX X1XXXX
	Conductive Heat Level 1, Up to 176° F/80° C (ANSI/ISEA 105-2016)
	CFIA

SIZES

ITEM #	SIZE	UPC
99-1-9860-7	S (7)	063344175360
99-1-9860-8	M (8)	063344175377
99-1-9860-9	L (9)	063344175384
99-1-9860-10	XL (10)	063344175391
99-1-9860-11	X2L (11)	063344257448

*Not all styles/sizes available in all regions.

PACKAGING

- + 12 PR per Polybag 120 PR per Carton
- + Vend Pack Option Available: Yes

*Bob Dale Gloves products are tested for cut and puncture resistance. These products ARE NOT CUT AND PUNCTURE PROOF. Do not use with moving blades, tools or serrated blades.
*Not Proposition 65 compliant.